



2345 LED is versatile in use. As a wall or ceiling luminaire it fulfils nearly any lighting task thanks to its multi-lumen technology with three levels from 1.000 to 2.000 lm. With multi-colour, two light colors are available in one luminaire. Application areas are corridors, staircases, entrance areas, humid environments and canopied outdoor areas. This will get the job done!

Why you'll get the job done with the 2345 LED wall and ceiling luminaire

- Flexible luminaire luminous flux setting (2,000 lm, 1,400 lm and 1,000 lm) thanks to multi-lumen technology.
- Thanks to Multicolour, two light colours in one luminaire.
- High IP protection rating (IP65) for canopied outdoor applications.
- 1:1 replacement of conventional luminaires offering time and cost savings during refurbishment.
- Theft protection through additional screw locking device.
- Optionally with integrated HF motion sensor.
- Reliable service life (50,000 h, L70).

2345 LED at a glance

Dimensions Ø 300 x 85 mm

Luminaire luminous fluxMultilumen: 2.000 lm / 1.400 lm / 1.000 lm

Colour Temperature Multicolour: 3.000 K / 4.000 K

Connected load 19 W, 12 W, 9 W

Protection rating, Safety class IP65 / IK10, SK II

Weight 0,8 kg

Service life 50.000 h (L70)

All variants of 2345 LED

product reference	тос	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions ØxH [mm]	Replacement W
Multi-colour + multi-lumen						
2345 G2 WD1 20/14/10/ML-8MC ET	7790640	2.000 / 1.400 / 1.000	19 / 12 / 9	4.000 / 3.000	300 x 85	1 x 18 / 1 x 26 / 2 x 18 / 2 x 26
Multi-colour / multi-lumen with Sensor						
2345 G2 WD1 20/14/10/ML-8MC ET+HFS	7790840	2.000 / 1.400 / 1.000	19 / 12 / 9	4.000 / 3.000	300 x 85	1 x 18 / 1 x 26 / 2 x 18 / 2 x 26

All technical data as well as weight details and dimensions are carefully created. Errors are not excluded. Product pictures are an example and may differ from the original. We reserve the right to make changes that serve progress.